



TYPE	BARREL DIA OF BOLTS "D"	GRIP "G"	Barrel length (L1)	THREAD LENGTH	TOTAL LENGTH	ROUND WASHER OUTER DIA(D1)	WASHER BORE DIA"d"	NOS REQD. FOR 17 SPAN
1	25.5	22	32	40	72	50	28	98
2	25.5	24	34	40	74	50	28	206
3	25.5	28	38	40	78	50	28	578
4	25.5	31	41	40	81	50	28	68
5	25.5	32	42	40	82	50	28	45
6	25.5	36	46	40	86	50	28	397
7	25.5	40	50	40	90	50	28	36
8	25.5	41	51	40	91	50	28	138
9	25.5	44	54	40	94	50	28	220
10	25.5	56	66	40	106	50	28	274
11	25.5	60	70	40	110	50	28	188
12	25.5	64	74	40	114	50	28	437
13	25.5	77	87	40	127	50	28	50
14	25.5	107	117	40	157	50	28	99
15	25.5	118	128	40	168	50	28	35
16	25.5	121	131	40	171	50	28	57
17	25.5	122	132	40	172	50	28	30
18	25.5	143	153	40	193	50	28	17
19	25.5	148	158	40	198	50	28	27
20	25.5	152	162	40	202	50	28	10
21	25.5	162	172	40	212	50	28	11

- NOTE: 1. ALL DIMENSION ARE IN MM
 2. T.F. BOLTS ARE GR.-8.8 AND NUTS ARE GR.8-CONFIRMING TO IS:1367 WITH MACHINED WASHER
 3. THESE BOLTS ARE REQD. FOR 17X121.6M SPAN TO REPLACE RIVETS

Requisition no: D/935 dt 18.04.2015

[Signature]
 18/04/2015