

LIST of FITTINGS
Requirement : 261 sets.

LIST OF FITTINGS FOR STEEL CHANNEL SLEEPER (One set)

Sl. No	Description of Parts		Drawing no	Specification	Nos
1	10 mm Grooved Rubber Pad for BG Running Rail	Non-Galvanized	R.D.S.O/T-5156	IRS Specification for 10 mm thick G.R.Pad (Provisional) 1999	2
2	M.S. Clip (Outer) for B.G. Running Rail	Galvanized	R.D.S.O/T-5157	IS : 2062 E 250 A/B	2
3	M.S. Clip (Inner) for B.G. Running Rail	Galvanized	R.D.S.O/T-5158	IS : 2062 E 250 A/B	2
4	Annular Cap	Galvanized	R.D.S.O/T-5159	IS : 2062 E 250 A/B	4
5	T-Head Bolt & Nut for BG Running Rail	Galvanized	R.D.S.O/T-5160	IRS T-10-1968	4
6	Tapper washer (For Guard Rail)	Galvanized	R.D.S.O/T-5161	IS : 2062 E 250 A/B	4
7	Tapper washer (For Guard Rail)	Galvanized	R.D.S.O/T-5162	IS : 2062 E 250 A/B	4
8	6 mm Grooved Rubber pad (for Guard Rail)	Non-Galvanized	R.D.S.O/T-5163	IRS Specification for 6mm. Thick G.R. Pad (Provisional-1980)	4
9	Bolt & Nut for Guard Rail	Galvanized	R.D.S.O/T-5164	IRS T-10-1968	4
10	Single Coil Spring washer	Galvanized	T - 10773	IS : 3063-1972	8
11	Tapped Split Pin	Galvanized	as suitable	IS 549	8
12	8th. Plain washer for BG Running Rail	Galvanized		IS : 2062 E 250 A/B	2
13	28mm dia. Hook Bolt 310 mm long	Galvanized	R.D.S.O/BA-1636/1/R2	IS : 2062 E 250 A/B	2
14	Nut for 28mm dia. Hook Bolt	Galvanized	R.D.S.O/BA-1636/1/R2	IS : 2062 E 250 A/B	4
15	Single Coil Spring washer (For 28mm dia Hook Bolt)	Galvanized	R.D.S.O/BA-1636/1/R2	IS 3063	6
16	Tapped Split Pin (For 28mm dia Hook Bolt)	Galvanized	R.D.S.O/BA-1636/1/R2	IS 549	2
17	25mm Thick Elastomeric Pad (25X300X245 mm)	Non-Galvanized	R.D.S.O - 1636/1/R RDSO/BA-1636/1/R2	IRS INSPECTION FOR 20/25MM THICK NYLON CORD REINFORCED ELASTIMERIC PAD (PROVISINAL) 1998 No. RDSO/M & C/CP-195/98	2